

HIGHLIGHTS

- Compact structure, light weight, accessible elevators.
- Motor and crawler drive, lower noise, stronger passability.
- Large capacity batteries, better endurance

Configurations Standard

Automatic Braking System
Extension Platform
Folding Guardrails
Charging Protection
Hour Meter
Motion Alarm
Horn
Emergency Stop Tilt Sensor
Safety Arm
Self-diagnosis
Platform Self-lock Door
Flashing Beacons
Emergency Descend

Optional


Working Lamp on the Platform
Load Sensing System
AC Power on the Platform
Air Pipe in the Platform



Electric Crawler Scissor Lift

MOBILE ELEVATING WORK PLATFORMS

MODEL	HC0507E	HS0610E	HC1216E	HC1216E-R	HC1416E-R
Max. Working Height	m 6,5	7,8	13,8	13,8	15,8
A-Max. Platform Height	m 4,5	5,8	11,8	11,8	13,8
B-Platform Length	m 1,34	1,67	2,26	2,26	2,64
C-Platform Width	m 0,72	0,74	1,12	1,12	1,12
Extension Size	m 0,6	0,9	0,9	0,9	0,9
D-Heights (Rails Up)	m 2,07	2,27	2,63	2,63	2,71
Height (Rails Down)	m 1,71	1,85	2,03	2,03	2,01
E-Overall Length	m 1,48	2,33	2,83	2,83	3,02
F-Overall Width	m 0,79	1,25	1,6	1,6	1,6
G-Ground Clearance	mm 0,07	0,09	0,15	0,15	0,146
PERFORMANCE					
Platform Capacity	kg 230	230	320	320	250
Extension Capacity	kg 113	113	113	113	113
Max. Occupancy (In/Out)	1/0	2/1	2/2	2/2	2/2
Max. Wind Speed	m/s 0	12,5	12,5	12,5	12,5
Max. Drive Speed (Stowed)	km/h 4	3,2	4	4	4
Turning Radius	Rotate in Place	Rotate in Place	Rotate in Place	Rotate in Place	Rotate in Place
Up/Down Time	s 25/22	23/22	65/60	65/60	76/53
Gradeability	% 25	40	40	40	40
Max. Slope	(°) 1,5/3	/	/	/	/
Leveling Angle Of The Legs	(°) /	8/14	8/14	8/14	8/14
Drive	Front Crawler	Front Crawler	Front Crawler	Front Crawler	Front Crawler
Clawler	mm 150 x 72 x 43	180 x 72 x 55	300 x 72 x 67	230 x 90 x 53	300 x 101 x 48
POWER					
Batteries	V/Ah 24/100	24/200	48/200	48/200	48/300
Charger	VAC/A 100-240/6,5	100-240/10	100-240/13,5	100-240/13,5	100-240/13,5
WEIGHTS					
Total Weight	kg 920	1900	3480	3660	4150



PT. HASTA KARYA ANANTA

SALES - RENTAL - SERVICE - SPAREPART - TRADE IN

Tel: +62 21-2986-0544, 45 | Email: manlift@hka.co.id

Website: www.manlift.co.id

Add: Jl. Benteng Betawi, RT.001/RW.015, Tanah Tinggi Kec. Tangerang, Kota Tangerang, Banten 15119, Indonesia



ALWAYS LIFTING ALWAYS GROWING

HIGHLIGHTS

- Crawler chassis capable of leveling the equipment on staggered-height surfaces.
- One-click vehicle leveling and strong gradeability for operations on slopes.
- Simple layout, easy maintenance, and service.
- Pure electric drive with zero emissions, low noise, and strong gradeability.
- Neutral steering feature suitable for complicated working conditions.
- Long battery endurance.

Configurations Standard

- Automatic Braking System
- One-Way Extension Platform
- Folding Guardrails
- Charging Protection System
- Proportional Control
- Emergency Decant System
- Motion Alarm
- Horn
- Emergency Stop
- Tilt Protection System
- Safety Access Support Bar
- Fault Diagnosis System
- Forklift Hole
- Flashing Beacons
- Hour Meter
- Load Sensing System


Optional

- AC Power to the Platform
- Air Pipe to the Platform



Auto Lever Crawler Scissor Lift MOBILE ELEVATING WORK PLATFORMS

MODEL		HC0607EA	HS1018EA
Max. Working Height	m	7,9	11,6
A-Max. Platform Height	m	5,9	9,6
B-Platform Length	m	1,63	2,27
C-Platform Width	m	0,74	1,4
Extension Size	m	0,9	0,9
D-Heights (Rails Up)	m	2,39	2,96/2,53
Height (Rails Down)	m	2	2,13/1,73
E-Overall Length (With Ladder)	m	2,02	2,67
F-Overall Width	m	1,47/1,3	1,73/2,01
G-Ground Clearance	mm	80	85
PERFORMANCE			
Platform Capacity	kg	250	320
Extension Capacity	kg	113	113
Max. Occupancy (In/Out)		2/1	2/1
Max. Drive Speed (Stowed)	km/h	2,4	2,4
Turning Radius		Rotate in Place	Rotate in Place
Up/Down Time	s	16/34	60/40
Gradeability	%	40	40
Drive		Rear Crawler	Rear Crawler
Clawler	mm	250 x 72 60	300 x 101 x 56
POWER			
Batteries	V/Ah	48/160	48/200
Charger	VAC/A	100-240/13,5	100-240/13,5
WEIGHTS			
Total Weight	kg	1890	3500



PT. HASTA KARYA ANANTA

SALES - RENTAL - SERVICE - SPAREPART - TRADE IN

Tel: +62 21-2986-0544, 45 | Email: manlift@hka.co.id

Website: www.manlift.co.id

Add: Jl. Benteng Betawi, RT.001/RW.015, Tanah Tinggi Kec. Tangerang, Kota Tangerang, Banten 15119, Indonesia